




BKL CONVERSION US TO EU MEASUREMENTS

		OVERALL LENGTH	CLAMPING LENGTH	RING WIDTH	BOTTOM OF MOUNT TO SCOPE TUBE	TURRET CLEARANCE	WEIGHT	RISER HEIGHT ADDS	OVERALL HEIGHT	OTHER	OTHER	OTHER
US	167	1 INCH	1 INCH				2.1 OUNCES	0.68 INCHES	0.76 INCHES			
EU		25.4	25.4				0.06	17.27	19.3			
US	169	4	4				3.1	0.68	0.76			
EU		101.6	101.6				0.09	17.27	19.3			
US	173	1.625	1.625				1.7	0.68	0.76			
EU		41.275	41.275				0.05	17.27	19.3			
US	181	0.6	0.6				1.5	0.68	0.76			
EU		15.24	15.24				0.04	17.27	19.3			
US	253	3	1.65	0.6	0.774	0.125	4.4					
EU		76.2	41.91	15.24	19.66	3.175	0.125					
US	254	4	1.65	0.6	0.774	0.125	5.1					
EU		101.6	41.91	15.24	19.66	3.175	0.145					
US	254-D7	4	1.65	0.6	0.974	0.125	5.1					
EU		101.6	41.91	15.24	24.74	3.175	0.145					
US	254H	4	1.65	0.6	0.974	0.125	5.1					
EU		101.6	41.91	15.24	24.74	3.175	0.145					
US	257	0.6	0.6	0.6	0.774		3.1					
EU		15.24	15.24	15.24	19.66		0.09					
US	257H	0.6	0.6	0.6	0.974		3.1					
EU		15.24	15.24	15.24	24.74		0.09					
US	258	1.263	1.263	1.263	0.774		3					
EU		32.08	32.08	32.08	19.66		0.085					
US	258H	1.263	1.263	1.263	0.974		3.2					
EU		32.08	32.08	32.08	24.74		0.091					
US	260	4	4	0.6	0.774	0.125	5.1					
EU		101.6	101.6	15.24	19.66	3.175	0.145					
US	260-D7	4	4	0.6	0.974	0.125	5.1					
EU		101.6	101.6	15.24	24.74	3.175	0.145					
US	260H	4	4	0.6	0.975	0.125	5.1					
EU		101.6	101.6	15.24	24.74	3.175	0.145					
US	261	4		0.6	0.774	0.125	4.2			SHORT CLAMP LENGTH: .75	LARGE CLAMP LENGTH: 1.62	EJECTION PORT LENGTH: 1.72
EU		101.6		15.24	19.66	3.175	0.119			19.05	41.91	43.69

BKL CONVERSION US TO EU MEASUREMENTS

		OVERALL LENGTH	CLAMPING LENGTH	RING WIDTH	BOTTOM OF MOUNT TO SCOPE TUBE	TURRET CLEARANCE	WEIGHT	RISER HEIGHT ADDS	OVERALL HEIGHT	OTHER	OTHER	OTHER
US	263	1	1	1	0.774		4.4					
EU		25.4	25.4	25.4	19.66		0.124					
US	263H	1	1	1	0.974		4.4					
EU		25.4	25.4	25.4	24.74		0.124					
US	264	1.53	1.53	1	0.774		3.4			OFFSET: 1.35	BASE AND RING CLAMP WIDTH: 6	
EU		38.86	38.86	25.4	19.66		0.0964		34.29	15.24		
US	264H	1.53	1.53	1.53	0.974		3.7					
EU		38.86	38.86	38.86	24.74		0.105					
US	274		2		0.774		5.5					
EU			50.8		19.66		0.156					
US	278	2.25	1	1	0.774		5.5			OFFSET: 1.25		
EU		57.15	25.4	25.4	19.66		0.156		31.75			
US	288	4	2.5	0.6	0.825	0.18	4.5					
EU		101.6	63.5	15.24	20.955	4.572	0.128					
US	300	0.6	0.6	0.6	0.979		3					
EU		15.24	15.24	15.24	24.74		0.085					
US	301	1	1	1	0.979		3.5					
EU		25.4	25.4	25.4	24.74		0.099					
US	302	2.25	1	1	0.979		6.2					
EU		57.15	25.4	25.4	24.74		0.176					
US	303	0.6	0.6	0.6	0.68		3					
EU		15.24	15.24	15.24	17.272		0.85					
US	304	1	1	1	0.68		3					
EU		25.4	25.4	25.4	17.272		0.85					
US	305	1.263	1.263	1.263	0.68		2.9					
EU		32.08	32.08	32.08	17.272		0.082					
US	306	1.53	1.53	1.53	0.68		3.4					
EU		38.86	38.86	38.86	17.272		0.096					
US	307	1.263	1.263	1.263	0.979		3.3					
EU		32.08	32.08	32.08	24.74		0.094					
US	308	1.53	1.53	1.53	0.979		3.9					
EU		38.86	38.86	38.86	24.74		0.111					

BKL CONVERSION US TO EU MEASUREMENTS

		OVERALL LENGTH	CLAMPING LENGTH	RING WIDTH	BOTTOM OF MOUNT TO SCOPE TUBE	TURRET CLEARANCE	WEIGHT	RISER HEIGHT ADDS	OVERALL HEIGHT	OTHER	OTHER	OTHER
US	354	4	1.65	0.6	0.68	0.125	4.2					
EU		101.6	41.91	15.24	17.272	3.175	0.119					
US	360	4	4	0.6	?	0.125	5.1					
EU		101.6	101.6	15.24	?	3.175	0.145					
US	374	2	0.6	0.6			4.5					
EU		50.8	15.24	15.24			0.128					
US	388	4	2.5	0.6		0.18	1.5					
EU		101.6	63.5	15.24		4.572	0.128					
US	454	4	1.65	0.6	0.774	0.125	4.2					
EU		101.6	41.91	15.24	19.66	3.175	0.119					
US	456	1	1				2.1	0.69	0.76			
EU		25.4	25.4				0.06	17.53	19.3			
US	460	4	4	0.6	0.774	0.125	5.1					
EU		101.6	101.6	15.24	19.66	3.175	0.145					
US	463	1	1	1	0.774		4.4					
EU		25.4	25.4	25.4	19.66		0.125					
US	466	1	1				2.1	0.68	0.76			
EU		25.4	25.4				0.06	17.27	19.3			
US	554	4	1.65				2.5	0.69	0.76			
EU		101.6	41.91				0.071	17.53	19.3			
US	558	4	1.65 AND .75				2.6	0.69	0.76	PORT CLEARANCE: 1.72		
EU		101.6	41.91 AND 19.05				0.074	17.53	19.3	43.69		
US	566	1	1				2.1	0.69	0.76			
EU		25.4	25.4				0.06	17.53	19.3			
US	568	4	4				3.1	0.69	0.76			
EU		101.6	101.6				0.088	17.53	19.3			